

DATA SHEET: TEMBREAK 2 E160-SJ MCCB

Código Larce P3:

0403001105 0403001107 0403001109 0403001111
0403001106 0403001108 0403001110

MCCB Electrical Characteristics to IEC 60947-2, EN 60947-2, JIS C 8201-2-1 ANN.1, NEMA AB-1

Frame Reference	Quantity	Unit	Condition	TB2 Lite 160
Max in (A) of Frame				160
Model				E160
Number of Poles				3, 4
Type				SJ
Nominal current ratings				
	I_n	(A)	50°C	25,40,63,80 100,125,160
Electrical characteristics				
Rated operational voltage	U_e	(V)	AC 50/60 Hz DC	525 250
Rated insulation voltage	U_i	(V)		690
Rated impulse withstand voltage	U_{imp}	(kV)		8
Ultimate breaking capacity (IEC, JIS, AS/NZS)	I_{cu}	(kA)	690V AC 525V AC 440V AC 400/415V AC 220/240V AC 250V DC	- 6 10 16 25 13
Service breaking capacity (IEC, JIS, AS/NZS)	I_{cs}	(kA)	690V AC 525V AC 440V AC 400/415V AC 220/240V AC 250V DC	- 3 5 8 13 7
Rated breaking capacity (NEMA)		(kA)	480V AC 240VAC	6 25
Protection				
Fixed thermal, fixed magnetic				-
Adjustable thermal, fixed magnetic				■
Utilisation category				A
Installation				
Front connection (FC)				■
Extension bar (FB)				•
Cable clamp (FW)				■ ①
Rear connection (RC)				•
Plug-in (PM)				-
DIN rail mounting (DA)				•
Dimensions	height	(mm)		130
	width	(mm)	3 pole, (1 pole) 4 pole	75 100
	depth	(mm)		68
Weight	weight	(kg)	3 pole, (1 pole) 4 pole	0.8 1.0
Operation				
Direct Opening Action				■
Toggle operation				■
Door mounted (HS) / Breaker mounted handle (HB)				•
Motor operation				-
Endurance	Electrical	cycles cycles	415V AC	10,000② 20,000

■ Standard • Optional - Not Available

① Factory-fit at time of order


② 14,000 ≤125A

DATA SHEET: TEMBREAK 2 E160-SJ MCCB

Outline Dimensions E160-SJ


ASL: Arrangement Standard Line H: Handle Frame Centre Line C: Handle Centre Line

Front connected




Rear connected

Detail of connecting part




Rated current (A)	A	B	C	D	E	F
16-50	10.5	6.5	4	13	16	4
63-160	12.5	8.5	4	13	16	5

Drilling plan (front view)



Panel cutout (front view)



Panel cutout dimensions shown give an allowance of 1.0mm or more around the handle escutcheon.

DATA SHEET: TEMBREAK 2 E160-SJ MCCB

Time/Current Characteristic Curves

E160-SJ

