

DATA SHEET: TEMBREAK 2 E250-SCF MCCB

Código Larce: 0403001222

MCCB Electrical Characteristics to IEC 60947-2, EN 60947-2, JIS C 8201-2-1 ANN.1, NEMA AB-1



Frame Reference	Quantity	Unit	Condition	TB2 Lite 250
Max In (A) of Frame				250
Model				E250
Number of Poles				3, 4
Type				SCF
Nominal current ratings				
	In	(A)	50°C	125,150,175 200,225, 250
Electrical characteristics				
Rated operational voltage	U _e	(V)	AC 50/60 Hz DC	525 250
Rated insulation voltage	U _i	(V)		690
Rated impulse voltage	U _{imp}	(kV)		8
Ultimate breaking capacity (IEC, JIS, AS/NZS)	I _{cu}	(kA)	690V AC 525V AC 440V AC 400/415V AC 220/240V AC 250V DC	- 6 10 16 25 13
Service breaking capacity (IEC, JIS, AS/NZS)	I _{cs}	(kA)	690V AC 525V AC 440V AC 400/415V AC 220/240V AC 250V DC	- 3 5 8 13 7
Rated breaking capacity (NEMA)		(kA)	480V AC 240VAC	6 25
Protection				
Fixed thermal, fixed magnetic				■
Adjustable thermal, adjustable magnetic				-
Utilisation category				A
Installation				
Front connection (FC)				■
Extension bar (FB)				●
Cable clamp (FW)				●
Rear connection (RC)				●
Plug-in (PM)				-
DIN rail mounting (DA)				-
Dimensions	height width	(mm) (mm)	3 pole 4 pole	165 105 140
Weight	depth weight	(mm) (kg)	3 pole 4 pole	68 1.5 1.9
Operation				
Direct Opening Action				■
Toggle operation				■
Door mounted (HS) / Breaker mounted handle (HB)				●
Motor operation				●
Endurance	Electrical Mechanical	cycles cycles	415V AC	6,000 18,000

■ Standard ● Optional - Not Available

DATA SHEET: TEMBREAK 2 E250-SCF MCCB

Outline Dimensions E250-SCF

ASL: Arrangement Standard Line H: Handle Frame Centre Line C: Handle Centre Line



DATA SHEET: TEMBREAK 2 E250-SCF MCCB

Time/Current Characteristic Curves E250-SCF

