

DATA SHEET: TEMBREAK 2 E250-SJ MCCB

Código Larce 4P: 0403001294
0403001295

MCCB Electrical Characteristics to IEC 60947-2, EN 60947-2, JIS C 8201-2-1 ANN.1, NEMA AB-1

Frame Reference	Quantity	Unit	Condition	TB2 Lite 250
Max In (A) of Frame				250
Model				E250
Number of Poles				3, 4
Type				SJ
Nominal current ratings				
	In	(A)	50°C	100,125, 160,200 250
Electrical characteristics				
Rated operational voltage	U _e	(V)	AC 50/60 Hz DC	525 250
Rated insulation voltage	U _i	(V)		800
Rated impulse voltage	U _{imp}	(kV)		8
Ultimate breaking capacity (IEC, JIS, AS/NZS)	I _{cu}	(kA)	690V AC	-
			525V AC	7.5
			440V AC	15
			400/415V AC	25
			220/240V AC	35
			250V DC	15
Service breaking capacity (IEC, JIS, AS/NZS)	I _{cs}	(kA)	690V AC	-
			525V AC	6
			440V AC	12
			400/415V AC	19
			220/240V AC	27
			250V DC	12
Rated breaking capacity (NEMA)		(kA)	480V AC	10
			240VAC	35
Protection				
Fixed thermal, fixed magnetic				-
Adjustable thermal, adjustable magnetic				■
Utilisation category				A
Installation				
Front connection (FC)				■
Extension bar (FB)				•
Cable clamp (FW)				•
Rear connection (RC)				•
Plug-in (PM)				-
DIN rail mounting (DA)				-
Dimensions	height	(mm)		165
	width	(mm)	3 pole	105
			4 pole	140
	depth	(mm)		68
Weight	weight	(kg)	3 pole	1.5
			4 pole	1.9
Operation				
Direct Opening Action				■
Toggle operation				■
Door mounted (HS) / Breaker mounted handle (HB)				•
Motor operation				•
Endurance	Electrical Mechanical	cycles cycles	415V AC	6,000 18,000


■ Standard • Optional - Not Available

DATA SHEET: TEMBREAK 2 E250-SJ MCCB

Outline Dimensions E250-SJ

ASL: Arrangement Standard Line H: Handle Frame Centre Line


Front connected



Rear connected

Drilling plan (front view)

Panel cutout (front view)




Panel cutout dimensions shown give an allowance of 1.0mm around the handle escutcheon.

DATA SHEET: TEMBREAK 2 E250-SJ MCCB


Time/Current Characteristic Curves

E250-SJ (100 ~ 200A)



Time/Current Characteristic Curves

E250-SJ (250A)



LARCE ELECTRIC